



LC-TV-2U.2U

Terminal

Plug-screw terminal 10pin
max. 1,5 qmm

Connector:

- 1 : input 1 +
- 2 : input 1 -
- 3 : output 1 +
- 4 : output 1 -
- 5 : input 2 +
- 6 : input 2 -
- 7 : output 2 +
- 8 : output 2 -

Power supply
9-10: supply 24V AC/DC

LED power supply

Technical Data

Input, channel 1-2	0- +-10V, 0-10V, 2-10V DC max. +12V DC
Input resistor	200 kOhm
Output, channel 1-2	0- +-10V, 0-10V, 2-10V DC
Output current	max. +6mA
Power supply	24V AC/DC, +-15%
Power current	max. 100mA
Precision	0,2%
Isolation in – out - supply	1000 Vss
Operating temperature	-10 - +50°C
Storage temperature	-30 - +80°C
Construction	PCB mount. TS35, EN50022
Weight	80g
Dimensions	24 x 72 x 94 mm (WxHxD)

Two channel Isolation amplifier, buffer amplifier, for DC voltage input.

Input value = output value, 0- +-10V, 0-10V, 2-10V.

Electrical isolation between input, output and power supply, three-port-isolation.

RINCK ELECTRONIC GMBH

Kleekamp 6

D-27356 Rotenburg (Wümme)

www.rinck-electronic.de

info@rinck-electronic.de

2 CHANNEL ISOLATION AMPLIFIER LC-TV-2U.2U

Input 1-2	0- +-10V, 0-10V or 2-10V DC
Output 1-2	0- +-10V 0-10V or 2-10V DC
Power supply	24 V AC/DC

B 152

E_LC-TV-
2U_2U

23.03.15